



Applications

- Radar/Sonar Beamforming
- ELINT
- Image/Video Processing
- Digital Signal Processing
- Data Encryption

Board Features

- Customised conduction-cooled heatplate
- Air-Cooled/Conduction-Cooled Options
- Separate PCI Express Bridge
- XRM2 I/O Interface

FPGA Features

- 3x PCI Express Gen3 x8 cores (6 for XCKU115)

Summary

The **ADA-VPX3-KU1** assembly is based on the Xilinx Kintex UltraScale range of Platform FPGAs, bringing together the power and configurability of the **ADM-XRC-KU1** FPGA module in a 3U VPX format.

Features include PCI Express Gen2 interface, external memory, high density I/O, system monitoring and flash boot facilities.

A comprehensive cross platform API with support for **Microsoft Windows, Linux and VxWorks** provides access to the full functionality of these hardware features.

Placing the PCI Express bridge in bypass allows the creation of a Gen 2 x8 PCI Express endpoint design directly into the target FPGA. Target FPGAs KU060 and KU115 can also support Gen3 x8 PCI Express designs.

The conduction-cooled variant uses a single-piece heatplate, profiled to match both the carrier and FPGA boards and provide optimal cooling performance.

Target Devices

Xilinx Kintex UltraScale: XCKU060 (FLVA1517)

LUTs = 221k(663k)

FFs = 663k(1326k)

DSPs = 2760(5520)

BRAM = 38.0Mb(75.9Mb)

3x PCI Express Gen3 x8 cores (6 for XCKU115)

Application Data Memory

4x SDRAM 2GB DDR4-2400

FPGA Configuration Memory

BPI 1Gbit Flash Memory
Configured as 2x Bridge

FPGA Configuration Modes

By PCI Express Bridge on power up
By software via PCI Express Bridge
Via External JTAG connector

Deliverables

ADA-VPX3-KU1 Board
One Year Warranty
One Year Technical Support

Host Interface

PCI Express Gen2 x1, x2 or x4 link to separate bridge device with 2GB/s local link to user FPGA
4 DMA Controllers
Interrupt Controller

Board Format

3U VPX (OpenVPX Compliant)

Input/Output Interfaces

146x LVCMOS/LVDS I/O (programmable to 1.2

8x High-Speed Serial Links to XRM2

10x High-Speed Serial Links via PnB connector

38x LVCMOS 3.3V GPIO connections via PnB connector (VITA 46.9 X8d+X12d+X38s compatible pinout)

64x Multiple LVCMOS/LVDS GPIO connections via optional PMC Pn4 connector (1.8V levels with 2.5V compatible inputs)

Note: only available with Pn4 Build Option selected

Support

The ADA-VPX3-KU1 is supplied with the ADMXRCG3 Support & Development kit (SDK) along with ADB3 Driver for Windows / Linux / VxWorks.

Environmental Specification
Temperature Ranges

Cooling Option	Operating Temperatures		Storage Temperatures	
	Min	Max	Min	Max
AC0	0°C	55°C	-40°C	85°C
AC1	-40°C	70°C	-55°C	100°C
CC1	-40°C	70°C	-55°C	100°C

Operating Humidity : Up to 95% (non-condensing)

EMC Standards

FCC 47CFR Part 2
EN55022:2010 Equipment ClassB

Conformal Coating Options

Acrylic or Polyurethane
Contact sales for specification of coatings.

Ordering Information

Order Code: ADA-VPX3-KU1/z-2(c)(a)(p)(IO)

Option	Code	Description of Options
Kintex Ultrascale device	z	KU060 = XCKU060 FPGA fitted, KU115 = XCKU115 FPGA fitted
Pn4 Fitted	p	blank = not fitted, /Pn4 = Pn4 connector fitted
Cooling	c	blank = air cooled commercial, /AC1 = air cooled industrial, /CC1 = conduction cooled industrial
Conformal coating	a	blank = no conformal coating, A = Acrylic, P = Polyurethane
IO Option	IO	blank = One differential pair on Pn6 designated as an external clock input, /10RX = External clock input replaced by 10th data input

Address: Suite L4A, 160 Dundee Street,
Edinburgh, EH11 1DQ, UK
Telephone: +44 131 558 2600
Fax: +44 131 558 2700
email: sales@alpha-data.com
website: http://www.alpha-data.com

Address: 611 Corporate Circle, Suite H
Golden, CO 80401
Telephone: (303) 954 8768
Fax: (866) 820 9956 - toll free
email: sales@alpha-data.com
website: http://www.alpha-data.com