


AD01255



Applications

- Digital Signal Processing
- Radar/Sonar Beamforming
- ELINT
- Image/Video Processing
- Data Encryption

Summary

The **ADM-VPX3-7V2** is a high performance reconfigurable 3U OpenVPX format board based on the Xilinx Virtex-7 range of Platform FPGAs.

Features include PCI Express Gen2 interface, external memory, high density I/O using a Vita 57 standard, high Pin Count FMC Interface, Gigabit Ethernet Interface, system monitoring and flash boot facilities.

A comprehensive cross platform API with support for **Microsoft Windows, Linux and VxWorks** provides access to the full functionality of these hardware features.

Placing the PCI Express bridge in bypass allows the creation of a Gen 2 x8 PCI Express endpoint design directly into the target FPGA (Target FPGAs VX330T and VX690T can also support Gen3 x8 PCI Express designs).

The **ADM-VPX3-7V2** is available in a cost reduced form without a separate Bridge FPGA for high-volume production orders. A Rear Transition Module (RTM) is available to accelerate development by providing monitor and control access to all Rear (backplane) IO signals.

Target Devices

Xilinx Virtex-7
 XC7V585T, XC7VX690T (FF(G)1761)
 LUTs = 582k FFs = 728k DSPs = 1260
 BRAM = 28.6Mb(52.9Mb)

3x PCIe® Gen2 (690T 2x Gen3)

Application Data Memory

4x 512MB DDR3-1600

Configuration Memory

BPI 512MBit Flash Memory
 Configured as 2x Bridge

Configuration Modes

PCI Express direct to SelectMAP port
 From Flash direct on power up
 External JTAG connector

Deliverables

ADM-VPX3-7V2 Board
 One Year Warranty
 One Year Technical Support

Board Features

- Separate PCI Express Bridge FPGA
- High-density FMC Interface
- 2GByte on-board DDR3-1600 SDRAM

Host Interface

PCI Express Gen2 x1, x2 or x4 link to separate bridge device with 2GB/s local link to user FPGA
 4 DMA Controllers
 Interrupt Controller

Input/Output Interfaces

Discrete Digital
 GPIO

High-Speed Serial Links

High-Speed Serial Links
 High-Speed Serial Links (compliant to VITA 46.9
 X24S+X12D+X8D)

Discrete Digital

GPIO (compliant to VITA 46.9 X24S+X12D+X8D)

Support

Comprehensive Software Development Kit with source code for example software and FPGA designs.

Board Format

3U VPX
(OpenVPX
Compliant) ERROR ERROR ERROR ERROR

Environmental Specification

Cooling Option	Operating Temperatures		Storage Temperatures	
	Min	Max	Min	Max
AC0	0°C	55°C	-40°C	85°C
ACE	0°C	70°C	-55°C	100°C
AC1	-40°C	70°C	-55°C	100°C
CC0	0°C	55°C	-40°C	85°C
CCE	0°C	70°C	-55°C	100°C
CC1	-40°C	70°C	-55°C	100°C

Operating Humidity : Up to 95% (non-condensing)

EMC Standards

FCC 47CFR Part 2
EN55022:2010 Equipment ClassB
EN55024:2010
EN60950-1:2006 (+A12:2011)

Conformal Coating Options

Acrylic or Polyurethane
Contact sales for specification of coatings.

Ordering Information

Order Code: ADM-VPX3-7V2/z-y(m)(c)(a)

Option	Code	Description of Options
Vertex-7 device	z	V585T=XC7V585T, VX690T=XC7VX690T
Vertex-7 speed	y	1, 2, 2G, 2L, 3
Memory	m	blank = 2GBytes on board SDRAM (Four banks of 512MBytes), /4 = 4GBytes on board SDRAM (Four banks of 1GByte)
Cooling	c	blank = air cooled commercial, /ACE = air cooled extended, /AC1 = air cooled industrial, /CC0 = conduction cooled Commercial, /CCE = conduction cooled Extended, /CC1 = conduction cooled industrial
Conformal Coating	a	blank = no conformal coating, A = Acrylic, P = Polyurethane
Note		not all FPGA speed grades available in all configurations. Contact Alpha Data for full details.

UK Office

Address: Suite L4A, 160 Dundee Street,
Edinburgh, EH11 1DQ, UK
Telephone: +44 131 558 2600
Fax: +44 131 558 2700
email: sales@alpha-data.com

USA Office

611 Corporate Circle, Suite H
Golden, CO 80401
(303) 954 8768
(866) 820 9956 - toll free
sales@alpha-data.com