

AD01152

Prime Application

IF/Baseband data signal generation


Board Features

- Dual 16-bit 1Gsp/s DACs
- External Clock Input

Summary

The XRM2-DAC-D4/1G is an XRM2 I/O Module, providing two Digital to Analog converters with 16-bit resolution and sampling rates up to 1GHz.

Aimed at IF/Baseband signal generation, provision is made for use of either an external or internally generated clock source. External trigger and auxiliary I/O ports are also provided.



Deliverables

XRM2-DAC-D4/1G Board
One Year Warranty
One Year Technical Support

Board Format

Alpha Data XRM2 I/O Module

Input/Output Interfaces

DAC

Dual 16-bit DACs up to 1GHz

Resolution: 16-bit

Max Sample Freq: 1000MHz

Bandwidth: 1MHz to 350MHz

Impedance: 50Ω (AC coupled)

Connector: SMA

External clock input

External clock input

Trigger I/O

Trigger I/O

Auxiliary I/O

Auxiliary I/O

Synchronisation I/O

Synchronisation I/O

Environmental Specification

Cooling Option	Operating Temperatures		Storage Temperatures	
	Min	Max	Min	Max
ACD	0°C	55°C	-40°C	85°C

Operating Humidity

Up to 95% (non-condensing)

EMC Standards

FCC 47CFR Part 2
EN55022:2010 Equipment ClassB

Ordering Information

Order Code: XRM2-DAC-D4/1G(u)

Option	Code	Description of Options
XRM2 Keying	u	blank = keyed connector, /U = unkeyed connector

UK Office

Address: Suite L4A, 160 Dundee Street,
Edinburgh, EH11 1DQ, UK
Telephone: +44 131 558 2600
Fax: +44 131 558 2700
email: sales@alpha-data.com

USA Office

611 Corporate Circle, Suite H
Golden, CO 80401
(303) 954 8768
(866) 820 9956 - toll free
sales@alpha-data.com