

Prime Application

SpaceWire Communications

Board Features


- 2-bit Serializer/Deserializer (SERDES) functionality
- LVDS Physical Layer
- Data rates to 200 Mbits/sec
- Data/Strobe transmit skew <500pS
- Each channel connected via 9-pin microD receptacle - compatible with STAR-Dundee cables



Summary

The XRM2-SPW is an IO Module which provides SpaceWire Interface capability for Alpha Data FPGA cards.

It provides the user with the ability to implement two SpaceWire Links. The links are Fully Isolated from the FPGA board (>1.0kV isolation rating) with power provided by a front panel connector.



Deliverables

XRM2-SPW Board
One Year Warranty
One Year Technical Support

Host Interface

Input/Output Interfaces

SpaceWire Transceiver

Environmental Specification

Cooling Option	Operating Temperatures		Storage Temperatures	
	Min	Max	Min	Max
AC1	-40°C	70°C	-55°C	100°C
CC1	-40°C	70°C	-55°C	100°C

Operating Humidity

Up to 95% (non-condensing)

EMC Standards

FCC 47CFR Part 2
EN55022:2010 Equipment ClassB

Ordering Information

Order Code: XRM2-SPW/U

UK Office

Address: Suite L4A, 160 Dundee Street,
Edinburgh, EH11 1DQ, UK
Telephone: +44 131 558 2600
Fax: +44 131 558 2700
email: sales@alpha-data.com

USA Office

611 Corporate Circle, Suite H
Golden, CO 80401
(303) 954 8768
(866) 820 9956 - toll free
sales@alpha-data.com